

Universal control units

public safety equipment

SW830-2

- universal use for almost any application
- 8 silicone backlit buttons with LED function indication and replaceable symbols
- 7 switches control panel with 3 x 0.2Amp and 4 x 0.1Amp outputs for auxiliary device power or function activation.
- 1 Programmable Short Cut Button for quick activation of pre-set buttons.
- Backlit rubber touch buttons.
- Fully programable buttons in ON/OFF or momentary switch mode.
- European Siren Interlock compatible.
- 10 LED signal indicator for your lightbar or traffic director.
- 35 selectable icon stickers to clearly label your panel
- dimensions (w x h x d): 95 x 69 x 26 mm



ID-11 Plus

- universal use for almost any application
- 11 silicone backlit buttons with LED function indication and replaceable symbols
- wide range of programmable functions, e.g. one of the programming options is the function of automatic siren deactivation in case of turning off the beacon and, conversely, automatic beacon activation with the button activating the siren.
- outputs:
 - 3x (10 A)
 - 3x (3 A)
 - 5x (0,2 A)
- ensures automatic beacon output when siren is activated
- supply voltage 10 - 24 V
- cable length 195 cm
- dimensions (w x h x d):
 - control panel 100 x 60 x 18,5 mm
 - fuse box 148 x 92 x 25 mm



HOLOMY s.r.o.

Hemy 829, Krásno nad Bečvou
757 01 Valašské Meziříčí
Česká republika

tel: +420 571 685 970
+420 571 685 971

e-mail: sales@holomy.cz
www.holomy.cz

Certifikát ISO 9001