

Warning lightbars series VxL(C)

public safety equipment



VNL 024LU-BbSbB-1092

Properties

- unique design offers variability of lightbar equipment and versions
- rust-proof solid aluminium base
- crash-resistant polycarbonate UV stabilised lenses
- homologated solution e.g. for work vehicles of emergency services - blue color for priority, amber for obstacle in the road
- color combinations also available for special purposes - vehicles FOLLOW ME at airports, etc.
- homologation:
 - EHK 65 - DAY / NIGHT operation - blue (TB2), red (TR2) and amber color (TA2)
 - EHK 10, EHK 26

Standard dimensions

- height 100 mm, depth 288 mm
- standard width 1092, 1192, 1492, 1704 mm
- special width 576, 972, 1362, 1898 mm



Basic lightbar configuration

- corners modules U-shaped - LEDs III. generation (dual or single row LED optics)
- colored or clear lenses
- center lens in clear, black, red, blue, amber or opal color



VSL 012 LU-BbSbB-2SP-1092



VSL 012 LU/HD-RrSbB-2S-1092

Equipment options

- integrated electronic siren in the lightbar
- integrated pressure loudspeaker in lightbar (single or double)
- LED single (STOP, STOP/POLICIE, AMBULANCE), or programmable warning displays (for height 80 mm only)
- side alley lights
- integrated SES module - synchronized external lights (mPower or nForce)
- possibility of automatic dimming
- inner directional warning LED modules
- inner white LED work lights
- LED arrowbar in center section (dual or single row optics) ●●●
- dual row LED optics
 - FD - LED MODULE consists of 6 LEDs into the „rectangle” ●●●●
 - HD - LED MODULE consists of 3 LEDs into the „triangle” ●●●
- two lightbars in one - allows any combination of two color LEDs on each side under clear end lenses such as red + blue, blue + amber



VNLC 024 LU-BASAB-FD-1362

HOLOMY s.r.o.

Hemy 829, Krásno nad Bečvou
757 01 Valašské Meziříčí
Česká republika

tel: +420 571 685 970
+420 571 685 971

e-mail: sales@holomy.cz
www.holomy.cz

Certifikát ISO 9001