

LED warning lights

public safety equipment

x- color code - blue (B), red (R), amber (A), clear(C)

LED (x) 44-II 12/24V

external use

- 12 LEDs
- corner warning light
- can be used as main warning system
- color: blue, red
- color of lens: clear or colored
- homologation EHK 65 (TB2, TR2)
- supply voltage 12 / 24 V
- max. current draw: 3,6 A / 12 V, 1,8 A / 24 V
- consumption in idle mode ~ 1mA
- dimensions (w x h x d): 92 x 125 x 56 mm
- weight 0,45 kg



external use

- 24 LED
- corner warning light
- can be used as main warning system
- color: blue, red
- color of lens: clear or colored
- homologation EHK 65 (TB2, TR2)
- max. current draw: 1,8 A
- dimensions (w x h x d): 92 x 250 x 56 mm
- weight 800 g


LED (x) 44 DUAL




LED (x) 53-mpower (x) (R65)

external use

- surface mount
- 6, 8, 12 LEDs - singleline version
- 16 LED - dualline version
 - Quick mount (QM)
 - Stud mount (STDM)
 - Screw mount (SCRM)
- color: blue, amber, red, white
 - + combination of colors
- homologation EHK 65 (XB2, XR2, XA2)
- silicone body
- supply voltage 12 / 24 V
- max. current draw:
 - 3",4": 1,56 A / 12 V, 0,78 A / 24 V
 - 4x2: 0,9 A / 12 V, 0,5 A / 24 V
- dimensions QM, STDM (w x h x d):
 - 3": 77 x 23 x 10 mm
 - 4": 103 x 23 x 10 mm
 - 4x2: 103 x 38 x 11 mm
- dimensions SCRM (w x h x d):
 - 3": 89 x 23 x 10 mm
 - 4": 114 x 23 x 10 mm
 - 4x2: 115 x 38 x 11 mm



LED (x) 53-mpower 3" (QM, STDM)



LED (x) 53-mpower 4" (QM, STDM)



LED (x) 53-mpower 4x2 (STDM)



LED (x) 53-mpower 3" (SCRM)



LED (x) 53-mpower 4" (SCRM)

Holders LED (x) 53-mpower (x) (R65)

- Window shroud for use with LED (x) 53-mpower STDM.
- Angle adjustment allows for a variety of placement options between 25 degrees and 90 degrees
- VHB dual-lock allows light to be flush mounted to window to prevent flashback
- Top, bottom or rear wire exits to allow for concealed wire
- single or dual version



- A 35 Degree wedge for mounting the SoundOff Signal mPower Fascia 4 light, with the Quick Mount variant, to sloped surfaces.



- light holder for windshield mounting
- easy installation under the car's ceiling trim
- for LED 53-mpower 4 "-STDM



- light holder for windshield mounting
- for LED 53-mpower 3 "-STDM
- easy installation under the car's ceiling trim
- for LED 53-mpower 4 "-STDM



LED (xx) 67-WR(xx)-SM-(V) R65

external use

- 6, 12 LED
- surface mount
- color: blue, red, amber + combination of two colors
- homologation EHK 65 (XB2, XR2, XA2)
- supply voltage 12 / 24 V
- max. current: 1,4 A / 12 V, 0,7 A / 24 V
- dimensions (w x h x d)
 - horizontal 130 x 28,5 x 13 mm
 - vertical 28,5 x 130 x 13 mm



Holders LED 67-WR(xx)

- window shroud for glass mounting with suction cups
- simple version
- for LED lamps 67-WR
- window shroud for glass mounting with suction cups
- dual version
- for LED lamps 67-WR
- window shroud for glass mounting
- simple version
- for LED lamps 67-WR



LED (x) 59-Bolt 2-SM R65

external use

internal use

LED (x) 56-ULT-SM R65

- 9 LEDs of one color
- 18 LEDs two-color combination
- surface mount
- color: blue, red, amber + combination of two colors
- ECE 65 homologation
- two levels of intensity (XB2, XR2, XA2)
- supply voltage 12 / 24 V
- max. current draw: 1,1 A / 12 V, 0,5 / 24 V
- dimensions (w x h x d) 129 x 41 x 13 mm



- 6 LEDs
- surface mount
- color: blue, red, amber
- homologation EHK 65 (XB1, XR1, XA1)
- supply voltage 12 / 24 V
- max. current draw: 0,75 A / 12 V, 0,4 V / 24 V
- dimensions (w x h x d): 91 x 28 x 7,5 mm



LED (x) 57-UT4-SM R65

external use

external use

LED (x) 57-UT6-SM R65

- 4 LEDs, surface mount
- color: blue, red, amber
- homologation EHK 65 (XB2, XR2, XA2)
- IP 67
- supply voltage 12 / 24 V
- max. current draw: 0,8 A / 12 V, 0,4 A / 24 V
- dimensions (w x h x d) 91 x 24 x 15 mm



- 6 LEDs, surface mount
- color: blue, red, amber
- homologations EHK 65 (XB2, XR2, XA2)
- IP 67
- supply voltage 12 / 24 V
- max. current draw: 1,1 A / 12 V, 0,5 A / 24 V
- dimensions (w x h x d) 123 x 24 x 15 mm



LED (x) 69-XF R65

external use

external use

LED (x) 55-ML6 R65

- 6 LED, external surface mount on vehicle body
- color: blue, red, amber
- homologation EHK 65 (XB2, XR2, XA2)
- supply voltage 12 V / 24 V
- max. current draw: 1 A / 12 V, 0,5 A / 24 V
- dimensions (w x h x d) 40 x 40 x 39 mm



- 3 LEDs, external surface mount on vehicle body
- color: blue, red, amber
- homologation EHK 65 (XB1, XR1, XA1)
- supply voltage: 12 / 24 V
- max. current draw: 1 A / 12 V, 0,5 A / 24 V
- dimensions (Ø x h) 35 x 30 mm



HOLOMY s.r.o.

Hemy 829, Krásno nad Bečvou
757 01 Valašské Meziříčí
Česká republika

tel: +420 571 685 970
+420 571 685 971

e-mail: sales@holomy.cz
www.holomy.cz

Certifikát ISO 9001