

LED warning displays

public safety equipment

OZN 102-UP

programmable display

14,5 W / 12 V / graphic display / internal/external use

- SMD LED with integrated graphics 30°
- possibility of mounting on a sun visor
- 40/56 columns of LEDs, 7/8 rows of LEDs
- dimensions (w x h x d)
 - OZN 102-UP-56/8-i-R/52mm - 442 x 87 x 17 mm, display area 388 x 52 mm
 - OZN 102-UP-56/7-i-R/54mm - 442 x 91 x 80 mm (including brackets), display area 388 x 54 mm
 - OZN 102-UP-56/8-i-R/65mm - 442 x 103 x 17 mm, display area 388 x 65 mm
 - OZN 102-UP-56/8-i-R/110mm - 580 x 150 x 30 mm, display area 476 x 110 mm
 - OZN 102-UP-40/8-i-R/65mm - 343 x 103 x 17 mm, display area 276 x 66 mm
 - OZN 102-UP-40/8-i-SC-R/65mm - 350 x 120 x 6,5 mm, display area 276 x 66 mm
 - OZN 102-UP-40/7-SC-R/56mm - 330 x 100 x 6,5 mm, display area 276 x 56 mm
 - OZN 102-UP-56/7-i-SC-R/54mm - 450 x 86 x 6,5 mm, display area 388 x 54 mm



OZN 102-UP-56/8-i-R/110mm



OZN 102-UP-56/8-i-R/52mm



OZN 102-UP-40/8-i-SC-R/65mm

OZN 102-UP flip-up mechanism

14,5 W / 12 V / graphic display / LED 2,5 mm / internal use

- SMD LED with integrated graphics 30°
- tilting mechanism suitable for concealed mounting
- motorised movement 5 W / 12V, zero consumption in sleep state
- choice of up to 200 inscriptions
- text display method:
 - static, running left, running right,
 - real or mirror text, inverse



- display area 476 x 110 mm
- matrix 56 x 8 LEDs
- dimensions - down (h x w x d): 465 x 48 x 155 mm



- display area 476 x 110 mm
- matrix 56 x 8 LEDs
- dimensions - down (h x w x d): 810 x 50 x 175 mm

OLED control panel

OZN 102

- control panel programmable by PC connection to the USB port of display:
 - OZN 102-UP**
- up to 200 combinations of text signs
- two-line OLED display shows the actual sign and next one to be activated
- text on the LED display can be programmed in the following versions:
 - static, alternating or running
- text display, easily readable even in bad light conditions
- easy to control by combined rotary and push-button
- dimensions: 107 x 68 x 23 mm



OLED control unit

Programming USB cable

- connects the control unit to the computer for easy custom programming of individual texts.
- CD with user program and drivers included

12 V / single horizontal line/ LED 3 mm / external/internal use

- SMD LED with integrated graphics 30°
- font height
 - fixed mount 50 mm
 - on a sun visor 46 mm
 - on a sun visor / dual vertical line 51,6 mm
- extremely high light output
- real or mirror text
- dimensions (w x h x d):
 - fixed mount:
 - 330 x 110 x 34 mm w. bracket
 - 330 x 110 x 15 mm w/o bracket
 - on a sun visor:
 - 300 x 110 x 4 mm
- x = language version
 - STOP - STOP
 - CZ - STOP/POLICIE
 - GB - STOP/POLICE
 - NL - STOP/POLITIE
- max. current draw 5 W



OZN 102-CZ-e-R



OZN 102-CZ-Z-i-SC-R

HOLOMY s.r.o.

Hemy 829, Krásno nad Bečvou
757 01 Valašské Meziříčí
Česká republika

tel: +420 571 685 970
+420 571 685 971

e-mail: sales@holomy.cz
www.holomy.cz

Certifikát ISO 9001