

Amber program

public safety equipment

VML(C) 012(024)L

LED

- homologation: EMC, EHK-65 (TA1)
- max. current draw:
 - 12 LEDs - 1,0 A / 12 V, 0,6 A / 24 V
 - 18 LEDs - 1,5 A / 12 V, 0,9 A / 24 V

magnetic (up to 250km/h) **M**

fixed mount **B**

fixed pipe mount **A**
(only for 90 mm)



magnetic base

VML(C) 012L(024L) - 90 mm:

- LEDs:** 12
- napájecí napětí:** 12 V or 24 V
- color:** amber
- fixed mount (B), magnetic (M), fixed pipe mount (A)
- diameter:** 180 mm
- height:** 98 mm (M), 90 mm (B), 160 mm (A)
- weight:** 1,7 kg (M), 1,1 kg (B), 1,8 kg (A)

VML(C) 012L(024L) - 140 mm:

- LEDs:** 18 or 24
- supply voltage:** 12 V or 24 V
- color of LEDs:**
 - amber: amber lens (VML)
 - clear lens (VMC)
- fixed mount (B), magnetic (M)
- diameter 180 mm
- height 155 mm (M), 140 mm (B)
- weight 2,1 kg (M), 1,7 kg (B)



VMLC 012L-A-12A

Telescopic mast for beacons,
code: 2005011575

VMC 012(024)L/NR

LED

- homologation: EMC, EHK-65
- LEDs:** 24
- color:** amber
- possibility to combine LED modules (e.g. blue/red beacon)
- consumption in idle mode ~ 1mA
- max. current draw: 3,6 A / 12 V, 1,8 A / 24 V

magnetic **M**

fixed mount **B**



VMC 024L/NR-FD-B-12B12R



VMC 024L/NR-FDH-B-12B12R

VMC 012L(024L) - low version:

- LEDs:** 12 or 24
- supply voltage:** 12 / 24 V
- fixed mount (B), magnetic (M)**
- diameter:** 220 mm, **height:** 105 mm (M), 93 mm (B)
- weight:** 1,9 kg (M), 1,3 kg (B)

VMC 012L(024L) - high version:

- LEDs:** 12 or 24
- supply voltage:** 12 / 24 V
- fixed mount (B), magnetic (M)**
- diameter:** 220 mm, **height:** 145 mm (M), 134 mm (B)
- weight:** 2,1 kg (M), 1,7 kg (B)

GUARDIAN

LED

- homologation: EMC, EHK-65
- two levels of intensity (TB2, TR2)
- LEDs:** 18, 36 or 72
- color:** amber
- possibility to combine LED modules (e.g. blue/red beacon)

magnetic **M**

fixed mount **B**

fixed pipe mount **A**

GUARDIAN-H - high version:

- LEDs:** 36 nebo 72
- supply voltage:** 12 / 24 V
- fixed mount (B), magnetic (M)
- diameter:** 148 mm
- height:** 107 mm (B), 113 mm (M)
- weight:** 0,8 kg (B), 1,1 kg (M)

GUARDIAN-L - low version:

- LEDs:** 18 or 36
- supply voltage:** 12 / 24 V
- fixed mount (B), magnetic (M), pipe mount (A)
- diameter:** 148 mm
- height:** 67 mm (B), 73 mm (M), 124 (A)
- weight:** 0,6 kg (B), 0,9 kg (M), 0,7 (A)



GUARDIAN-H - high version



GUARDIAN-L - low version

EVOLUX F 024L

LED

- 8 LEDs
- homologation: EMC, EHK-65
 - one level of intensity (TA1)
- color:** amber
- supply voltage:** 12 / 24 V
- max. current draw 2,3 A / 12 V, 1 A / 24 V
- synchronization of up to 4 beacons
- dimensions:
 - diameter: 116 mm (M, B, A)
 - diameter of base: 148 mm (B)
 - height 110 mm (M), 89 mm (B), 131 mm (A)
 - weight 0,86 kg (M), 0,43 kg (B), 0,46 kg (A)

magnetic **M**

fixed mount **B**

fixed pipe mount **A**



LED

B18-VMD 024L

M magnetic
B fixed mount
A fixed pipe mount

- 15 LEDs
- homologation: EMC, EHK-65
 - one level of intensity (TA1)
- color:** amber
- supply voltage:** 12 / 24 V
- max. current draw: 1,86 A / 12 V, 0,93 A / 24 V
- dimensions: diameter of base: 142 mm (B), 118 mm (M, A)
 - height: 116 mm (B,M), 154 mm (B), 194 mm (A)
 - weight: 1 kg (M), 0,7 kg (B), 0,8 kg (A)



LED arrowbar 6 / 8 modules

external use

LED A TC 56 / 58

- 6 (TC 56) or 8 (TC 58) LED modules
- supply voltage 12 / 24 V
- homologation EHK 65
- max. current draw 1,8 A / 6 modules, 2,3 A / 8 modules
- arrow left / right, warning flash mode, center out mode, selectable flash patterns
- amber color + optional combination with end warning modules
- dimensions (width x height x depth): version with 6 modules: 806 x 58 x 70 mm
version with 8 modules: 1075 x 58 x 70 mm



unit control

COMET LED

LED

- homologation: EMC, EHK-65
 - one level of intensity (TA1)
- color: amber
- supply voltage 12 / 24 V

magnetic (do 250 km/h) **M**
fixed pipe mount **A**
flexible pipe mount **AF**

- max. current draw: 0,9 A / 12 V, 0,5 A / 24
- dimensions:
 - diameter 165 mm
 - height 187 mm (M), 240 mm (A, AF)
 - weight 1,5 kg (M), 1,4 kg (A, AF)



PB-VMD (x)L-B-36A

LED

- 36 LEDs
- homologation: EMC, EHK-65
- color: amber
- supply voltage 12 or 24 V

fixed mount **B**

- IP 67
- max. current draw: 0,71 A / 12 V, 0,36 A / 24 V
- diameter base 75 mm
- weight: 20 mm



Warning lightbars series Magnum

LED

- high energy efficiency
- low aerodynamic resistance
- easy installation and maintenance
- rust-proof solid aluminium base, durable polycarbonate UV stabilised lenses

Dimensions

- height: 58 mm
- depth: 312 mm
- width: 584, 743, 902, 1060, 1219, 1378, 1537, 1695, 1854 mm

Basic lightbar configuration

- corners modules V-shaped - LEDs
- colored or clear lenses



VNT 024LU/MG-AA-1219/E

Equipment options

- inner directional warning LED modules - 3LEDs or 6LEDs
- side alley lights
- integrated SES module - synchronization of external lamps (mpower, nFORCE)
- inner white LED work lights
- LED arrowbar in center section (dual or single row optics)
- possibility of dualcolor of inner module
- possibility of automatic dimming of DIM

Warning lightbars series V(x)T

LED

- high energy efficiency
- low aerodynamic resistance
- easy installation and maintenance
- rust-proof solid aluminium base, durable polycarbonate UV stabilised lenses

Dimensions

- height 80 mm (V(x)T / 80) or 60 mm (V(x)T / 60)
- depth 288 mm
- width: standard 1089, 1229, 1528 mm
on order 492 (only for height 60 mm), 589, 989, 1409, 1708, 1908 mm

Basic lightbar configuration

- corners modules U-shaped - LEDs
- amber or clear lenses
- center lens in clear, black, red, blue, amber or opal color



VNT 024LU/60-AaaaCaaaA - 1704 mm

Equipment options

- LED single (STOP, STOP/POLICIE, AMBULANCE), or programmable warning displays (for height 80 mm only)
- side alley lights
- inner directional warning LED modules
- inner white LED work lights
- LED arrowbar in center section
- lightbar 492 mm (SLE) possibility of magnetic attachment (with safety cable)



VNT 012LU AA-4M-SLE



VNT 012LU/80-ACA-TM61-1089 mm

Warning lightbars series V(x)L

LED

- unique modular design offers variability of lightbar configurations and equipment
- durable polycarbonate UV stabilised lenses

Dimensions: height 100 mm, depth 288 mm, standard width 1092, 1192, 1492 mm
on order width: 576, 972, 1362, 1704, 1898 mm

Basic lightbar configuration

- **V(x)L LU**
 - corners modules U-shaped - LEDs
 - colored or clear lenses
 - center lens in clear, black, red, blue, amber or opal color

Equipment options

- LED single (eg FOLLOW ME), or programmable warning displays (for height 80 mm only)
- side alley lights
- inner directional warning LED modules
- inner white LED work lights
- LED arrowbar in center section



VNL 024LU AaCaA 1192

HOLOMY s.r.o.

Hemy 829, Krásno nad Bečvou
75701 Valašské Meziříčí
Česká republika

tel: +420 571 685 970
+420 571 685 971

e-mail: sales@holomy.cz
www.holomy.cz

Certifikát ISO 9001